

# ROS Topics

This page is a description of all the topics we are using (or plan to use) on the sub. Below is a symbolic representation of data flow on the sub (with sensors as we have right now).



## Sensors

### /orientation

Message: [geometry\\_msgs/Quaternion](#)

The current orientation of the sub, given as a quaternion. Any code wanting to know the sub's orientation should use this topic, not /orientation/rpy.

### /pretty/orientation

Message: [robosub/Euler](#)

The current orientation of the sub, given in roll, pitch, yaw. This is meant just for human readability of the sub's orientation, code should use the /orientation topic.

### /depth

Message: [std\\_msgs/Float32](#)

The current depth of the sub.

## Movement

### /thruster

Message: [robosub/thruster](#)

Dynamic array of commands going to the thrusters. Order of the thrusters is dependent on their order in the settings file.

### /control

Message: [robosub/control](#)

Send messages to this topic to move the sub around, the control system subscribes to this topic.

## /joystick\_driver

Message: [robosub/joystick](#) This is the raw joystick state, published by the joystick driver. Shows the current state of all axes and buttons on the joystick.

## /gamepad\_driver

Message: [robosub/gamepad](#) This is the raw gamepad state, published by the gamepad driver. Shows the current state of all axes and buttons on the gamepad.

# Vision

## /camera/(left|right|bottom)/image

Message: [wfov\\_camera\\_msgs/WFOVImage](#)

Images from our cameras.

## /vision

Message: [rs\\_yolo/DetectionArray](#)

Results of the deep vision processing system. It's a list detailing all the objects it sees.

# Hydrophones

## /hydrophones/[Frequency]/deltas

Message: Duplicated for all frequencies in the pool. Contains the latest time deltas between the reference and other 3 hydrophones.

```
Header header
duration d1
duration d2
duration d3
```

## /hydrophones/[Frequency]/timestamps

Message: Duplicated for all frequencies in the pool. Contains the latest timestamps recorded by the system.

```
Header header
Time ref
```

```
Time t1
Time t2
Time t3
```

## /hydrophones/[Frequency]/debug

Message: Used for debugging the hydrophone system.

```
Header header
Int64 frequency
Int64 avg_sig_strength
Float64 approx_angle
```

## /hydrophones/bearing

Message: [geometry\\_msgs/Vector3Stamped](#)

A 3-dimensional vector pointing at the pinger in  $i,j,k$  notation.

From:

<http://robosub-old.eecs.wsu.edu/wiki/> - **Palouse RoboSub Technical Documentation**

Permanent link:

[http://robosub-old.eecs.wsu.edu/wiki/cs/topics\\_list/start?rev=1506035579](http://robosub-old.eecs.wsu.edu/wiki/cs/topics_list/start?rev=1506035579)

Last update: **2017/09/21 16:12**